


## Grado 8 Gunnebo KLFU eslabón corto



REFERENCIA		DIMENSIONES DEL ES LABÓN			CARGA DE ROTURA	PESO	LONGITUD
nº artículo	código	diámetro (d) mm	paso (p) mm	ancho (w) mm	toneladas	kg/m	estándar m
Z802330	KLFU-10-8	10	30	14.6	12.6	2.2	1 x 100
Z802331	KLFU-13-8	13	39	18.4	21.4	3.7	1 x 100
Z801146	KLFU-16-8	16	48	22.6	32.2	5.8	1 x 100
Z327377	KLFU-19-8	19	57	26	45.4	8.0	1 x 100
Z327385	KLFU-22-8	22	66	30	61.0	11.0	1 x 50
Z801505	KLFU-26-8	26	78	35	86.0	14.8	1 x 50

## Grado 8 Gunnebo MLFU eslabón medio




REFERENCIA		DIMENSIONES DEL ES LABÓN			CARGA DE ROTURA	PESO	LONGITUD
nº artículo	código	diámetro (d) mm	paso (p) mm	ancho (w) mm	toneladas	kg/m	estándar m
Z802332	MLFU-10-8	10	40	14	12.6	2.0	1 x 100
Z802333	MLFU-13-8	13	55	20	21.4	3.3	1 x 100
Z800564	MLFU-16-8	16	65	22	32.2	5.0	1 x 100
Z800476	MLFU-19-8	19	75	29	45.4	7.1	1 x 100
Z800661	MLFU-22-8	22	88	30	61.0	9.4	1 x 50
Z801770	MFLU-26-8	26	91	35	86.0	13.9	1 x 50

## Grado 8 Gunnebo LLU eslabón largo




REFERENCIA		DIMENSIONES DEL ES LABÓN			CARGA DE ROTURA	PESO	LONGITUD
nº artículo	código	diámetro (d) mm	paso (p) mm	ancho (w) mm	toneladas	kg/m	estándar m
Z801933	LLU-6-8	6	35	10	4.5	0.6	5 x 100
Z801934	LLU-9-8	9	53	15	10.2	1.4	4 x 100
Z801935	LLU-11-8	11	64	18	15.4	2.1	4 x 100
Z801936	LLU-13-8	13	80	22	21.4	2.9	3 x 100
Z802160	LLU-16-8	16	100	27	32.2	4.6	1 x 100
Z601983	LLU-19-8	19	100	28	45.4	6.5	1 x 100
Z700526	LLU-22-8	22	120	36	61.0	8.7	1 x 50

## Grado 100 Trawlex eslabón corto



REFERENCIA		CADENA	DIMENSIONES			CARGA DE ROTURA		PESO	LONGITUD
nº stock	nº ref.	diámetro mm	paso mm	ancho mm	Trawlex®	calidad 80	kg	estándar m	
2781650	10030RTO	10	30	14	15.5	12	2.2	200	
2781652	13039RTO	13	39	18.1	26.5	20	3.61	150	
2781635	16048RTO	16	48	22.4	41	30	5.41	110	
2781644	19057RTO	19	57	26.6	57	45	7.81	75	


## Grado 100 Trawlex eslabón medio



REFERENCIA		CADENA	DIMENSIONES			CARGA DE ROTURA		PESO	LONGITUD
nº stock	nº ref.	diámetro mm	paso mm	ancho mm	Trawlex®	calidad 80	kg	estándar m	
2784579	10040RTO	10	40	15	15.5	12	1.85	250	
2784561	13052RTO	13	52	19.5	26.5	20	3.21	150	
2784507	16064RTO	16	64	22.4	41	30	4.86	110	
2784516	16064RTO	16	64	22.4	41	30	4.86	600	
2781653	16064PTO	16	64	22.4	41	30	4.86	110	
2784534	16064PTO	16	64	22.4	41	30	4.86	600	
2784570	19076RTO	19	76	27	57	45	6.92	75	
2784525	19076RTO	19	76	27	57	45	6.92	300	
2781662	19076PTO	19	76	27	57	45	6.92	75	
2784543	19076PTO	19	76	27	57	45	6.92	300	
2781671	22086RTO	22	86	26	75	60	9.24	60	
2784552	22086RTO	22	86	26	75	60	9.24	110	
2781680	26092RTO	26	92	30	95	85	13.66	50	

■ Denota Profile Chain™

## Grado 100 Trawlex eslabón largo



REFERENCIA		CADENA	DIMENSIONES			CARGA DE ROTURA		PESO	LONGITUD
nº stock	nº ref.	diámetro mm	paso mm	ancho mm	Trawlex®	calidad 80	kg	estándar m	
2781699	09053RTO	9	53	15	12.5	10	1.36	200	
2781706	11063RTO	11	63	18	18.5	15	2.03	150	
2781715	13080RTO	13	80	22	26.5	20	2.83	150	
2781720	13080RTO	13	80	22	26.5	20	2.83	600	
2784339	16100RTO	16	100	24.5	40	30	4.34	100	
2784348	16100RTO	16	100	24.5	40	30	4.34	600	
2781724	16100PTO	16	100	24.5	40	30	4.34	100	
2784320	16100PTO	16	100	24.5	40	30	4.34	600	
2784357	19100RTO	19	100	25	57	45	6.31	108	
2781733	19100PTO	19	100	25	57	45	6.31	108	
2781742	22120RTO	22	120	35.5	70	60	8.74	70	
2781751	28150RTO	28	150	46	105	95	14.41	50	
2781680	26092RTO	26	92	30	95	85	13.66	50	

■ Denota Profile Chain™


# CADENA GRADO 7

Tuna Chain



Galvanizado por inmersión en caliente (HDG)


## Grado 7 Gunnebo KLFZ eslabón corto




REFERENCIA		DIMENSIONES DEL ES LABÓN			CARGA DE ROTURA	PESO	LONGITUD
nº artículo	código	diámetro (d) mm	paso (p) mm	ancho (w) mm	toneladas	kg/m	standard m
Z800666	KLFZ-10-7	10	30	14.6	11	2.2	1 x 100 m
Z802329	KLFZ-13-7	13	39	18.4	18	3.7	1 x 100 m
Z801644	KLFZ-16-7	16	48	22.6	28	5.8	1 x 100 m
Z801409	KLFZ-17-7	17	48	24	30	6.4	1 x 100 m
Z801407	KLFZ-19-7	19	57	26	40	8.0	1 x 100 m

## Grado 7 Gunnebo MLFZ eslabón medio

REFERENCIA		DIMENSIONES DEL ES LABÓN			CARGA DE ROTURA	PESO	LONGITUD
nº artículo	código	diámetro (d) mm	paso (p) mm	ancho (w) mm	toneladas	kg/m	standard m
Z801561	MLFZ-10-7	10	40	14	11	2.0	1 x 100 m
Z802335	MLFZ-13-7	13	55	20	18	3.3	1 x 100 m
Z801645	MLFZ-16-7	16	65	22	28	5.0	1 x 100 m
Z801477	MLFZ-19-7	19	75	29	40	7.1	1 x 100 m



## Grado 6/7 Gunnebo LLZ eslabón largo



REFERENCIA		DIMENSIONES DEL ES LABÓN			CARGA DE ROTURA	PESO	LONGITUD
nº artículo	código	diámetro (d) mm	paso (p) mm	ancho (w) mm	toneladas	kg/m	standard m
Z487081	LLZ-6-7	6	35	10	3.9	0.6	1 x 100 m
Z801553	LLZ-9-7	9	53	15	9	1.4	1 x 100 m
Z360314	LLZ-11-7	11	64	18	13	2.1	4 x 100 m
Z800676	LLZ-13-6	13	80	22	16	2.9	3 x 120 m
Z801567	LLZ-16-6	16	100	27	24	4.6	1 x 100 m
Z801458	LLZ-19-6	19	100	28	34	6.5	1 x 100 m
Z801887	LLZ-22-6	22	120	36	46	8.7	1 x 50 m